

# Keypad Deadbolts

## BE365 Keypad Deadbolt with Turn-Lock Feature

#### Professional Grade Security For the Home

Schlage Keypad Deadbolts bring professional grade security with the convenience of keyless access to the home. The innovative Turn-Lock feature allows the user to lock and leave without a key. Ideal for front, back and side entry doors where deadbolts are required.

Exterior





Interior

### Security and Quality

- Grade 2 ANSI/BHMA certified
- Patented commercial grade clutching motor drive; tested to one million cycles
- Vandal resistant free-spinning deadbolt turn
- Code control; 6-digit programming code required to add and delete user codes
- Warning sounds after four incorrect codes entered; keypad disabled for 30 seconds
- · Mechanical key override; patent pending

#### Convenience

- Convenient keyless access; no keys to hide, lose or forget
- Pre-set with random 6-digit programming code and two random 4-digit user codes
- 19 user code capacity; 10,000 user code combinations
- Easily programmed right at the keypad; no need to remove inside escutcheon
- Blue LEDs illuminate the keypad on demand
- Locks can be re-keyed to match existing locks
- 9-volt alkaline battery included



Style shown: Camelot Satin Nickel

#### Easy to Install and Operate



• Fits most standard door preps; no need to drill additional holes



One-tool installation;
use just a screwdriver on pre-prepped doors



9-volt battery operation;
no special wiring required

# BE365 Keypad Deadbolt

#### **Certifications and Standard Features**

- Latch: 1" x 2-1/4" radius corner faceplate, 1" Housing Diameter -Requires 1" Edge Bore, 1" throw with Triple-Option™ square corner, radius corner and circular drive-in faceplates
- Strikes:  $1-\frac{1}{8}$ "x  $2-\frac{3}{4}$ ", square corner, no box, latch strike
- Backset: Adjustable backset, fits 2-3/8" to 2-3/4" backsets
- Cylinder: 5-pin solid brass, keyed 5-pin, C keyway, keyed different (KD)
- Door range: 1-3/8" to 1-3/4"
- Keys: Nickel silver cut keys, 5-pin, C-section
- Codes: Pre-set, random, six-digit programming code, two pre-set four-digit user codes (19 code capacity)
- Minimum 5-1/2" center-to-center distance between cross bore holes
- 9-volt battery included with average three-year battery life
- All-metal chassis and escutcheons
- Silicone rubber, wear-resistant buttons with LED backlight
- A 156.5-2001 Grade 2 auxiliary locks
- FCC Part 15
- CE Mark
- Available UL LISTED (Box Pack Only)







BE365

Deadbolt



FBF365



FBF365

by Lever



FF365





Locks are furnished with standard

specify exact features desired.

FF365

by Lever

features unless otherwise specified. To order locks with non-standard features,

FF285

by Knob



FF285

by Lever

Finishes	Availabl

15 H 1	Ultima™ Bright Brass 505	Antique Brass	Oil-Rubbed Bronze	Aged Bronze	Satin Nickel 619	Antique Pewter	Bright Chrome	Satin Chrome
eypad Deadbolts	505	609	613	716	619	620	625	626
BE365 PLY	V + B	V + B	В	V + B	V + B	V + B	V + B	V + B
BE365 CAM	V + B	V + B	В	V + B	V + B	V + B	V + B	V + B
eypad Security Set								
FBE365 PLY x PLY	٧							
FBE365 PLY x FLA	٧	٧		٧	٧	٧	٧	٧
FBE365 CAM x ACC	V	٧		٧	٧	٧	٧	V
FBE365 PLY x ORB (Canada)	٧							٧
eypad Front Entry - Whole Sets								
FE365 PLY x PLY	٧							
FE365 PLY x FLA	٧			٧	٧			
FE365 CAM x ACC	٧			٧	٧			
FE365 CAM x GEO		٧						
FE365 PLY x ORB (Canada)	٧							
eypad Front Entry - Bottom Half H	landleset (Lever han	ding must be	e specified)					
FE285 PLY x PLY	В		В					
FE285 PLY x FLA	В	В	В	В	В	В	В	В

#### Warranty

FE285 CAM x ACC

Schlage extends to the original consumer user of our Schlage brand product a lifetime limited mechanical and finish warranty against defects in material and workmanship. Exception: Schlage extends to the original consumer user of our Schlage brand product a one-year electronics warranty against defects in material and workmanship.

US Customer Service: 800-847-1864

Canada Customer Service (Commercial): 800-900-4734 Canada Customer Service (Residential): 800-811-8390

www.schlage.com



V = Retail Visual Pack B = Box Pack