

# XPass D2

Outdoor Compact RFID Reader



XPass D2 is an outdoor compact RFID reader based on Suprema's state-of-the-art RFID technology and multi-hardware platform, optimized for centralized access control systems such as Suprema's CoreStation. Using multi-form factor technology, mullion-type, gangbox-type and gangbox keypad-type are all supported. With dual-frequency (125kHz / 13.56MHz) RFID technology, XPass D2 also supports mobile cards using NFC and BLE, the latest mobile communication technologies. Packed in a rugged IP65/IP67 rated dust & waterproof performance as well as IK08 rated vandal-proof structure, suitable for tough environment and outdoor installation.

# XPass D2

## Outdoor Compact RFID Reader

### Features



Mobile card (NFC and BLE)



IP67 - Water and dust proof



Industry standard communication via OSDP



IK08 - Vandal proof



Multi-type hardware structure



Multi-class RFID card reading






Enhanced security with the Secure Element



Issue the smart card by using BioStar 2

### Product Specification

Item	 XPD2-MDB	 XPD2-GDB	 XPD2-GKDB
125kHz card compatibility	EM	EM	EM
13.56MHz card compatibility	MIFARE, MIFARE Plus, DESFire/EV1, FeliCa	MIFARE, MIFARE Plus, DESFire/EV1, FeliCa	MIFARE, MIFARE Plus, DESFire/EV1, FeliCa
Mobile card	NFC, BLE	NFC, BLE	NFC, BLE
IP rating	IP67	IP67	IP67
IK rating	IK08	IK08	IK08
Installation type	Mullion	Gangbox	Gangbox
Keypad	-	-	Supported (3x4)
RS-485	1ch (OSDP compatible)	1ch (OSDP compatible)	1ch (OSDP compatible)
Wiegand	1ch output	1ch output	1ch output
TTL	1 tamper output, 3ch LED, buzzer control	1 tamper output, 3ch LED, buzzer control	1 tamper output, 3ch LED, buzzer control
Sound	Multi-tone buzzer	Multi-tone buzzer	Multi-tone buzzer
Operating Temperature	-35°C ~ 65°C	-35°C ~ 65°C	-35°C ~ 65°C
Operating Humidity	0% ~ 95%, non-condensing	0% ~ 95%, non-condensing	0% ~ 95%, non-condensing
Power	DC 12V	DC 12V	DC 12V
Dimensions (WxHxD, mm)	48 x 144.7 x 27	80 x 130 x 25	80 x 130 x 25
Certificates	CE, FCC, KC, RoHS, REACH, WEEE, SIG	CE, FCC, KC, RoHS, REACH, WEEE, SIG	CE, FCC, KC, RoHS, REACH, WEEE, SIG



#### Suprema Inc.

17F Parkview Tower, 248, Jeongjail-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13554, Rep. of KOREA

Tel: +82 31 783 4502 | Fax: +82 31 783 4503 | Inquiry: sales@supremainc.com | [www.supremainc.com](http://www.supremainc.com)

©2018 Suprema Inc. Suprema and identifying product names and numbers herein are registered trademarks of Suprema, Inc. All non-Suprema brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.

[AHL-XPD2-180329-01-EN]